SOFTWARE DESIGN DOCUMENT FOR THE FACILITY IDENTIFICATION INITIATIVE (FII)

CONTRACT NO. 68-W1-0055 DELIVERY ORDER NO. 091

Prepared for:

United States Environmental Protection Agency Office of Information Resources Management 401 M Street, SW. Washington, DC 20460

Delivery Order Project Officer:

Charles D. Catlin

Prepared by:

EPA Systems Development Center
(A Contractor Operated Facility)
Science Applications International Corporation
200 North Glebe Road, Suite 300
Arlington, VA 22203

CONTENTS

1.0	INT	RODUCTION	1		
	1.1	Background	2		
	1.2	Purpose	2		
	1.3	Scope	2		
	1.4	Identification	2		
	1.5	System Overview	2		
	1.6	Assumptions	4		
	1.7	Constraints	5		
	1.8	User Community	6		
2.0	REF	ERENCES	6		
3.0	SYS	ΓΕΜ DESCRIPTION	7		
	3.1	System Operation			
	3.2	Equipment			
	3.3	Support Software			
4.0	SOFTWARE PRODUCT DESCRIPTION				
	4.1	Data Requirements	9		
	4.2	Interface Processes	9		
		4.2.1 Envirofacts Program Office Systems	9		
		4.2.2 States and Non-Envirofacts Program Office System Facility Data	9		
		4.2.3 Data Maintenance	10		
		4.2.4 Dun and Bradstreet Data	11		
		4.2.5 Locational Reference Tables	11		
	4.3	Functional Components	12		
		4.3.1 Facility Maintenance	12		
		4.3.2 Core FII Data Maintenance	16		
		4.3.3 Relink/Move Facilities	16		
		4.3.4 User Administration	16		
		4.3.5 Facility Search Components	19		
		4.3.6 Reporting Capability	21		
		4.3.7 Resolution of State and Program Office System Facility Data	22		
	4.4	Data Validation	26		
	4.5	Discrepancy Reporting and Processing	27		
	4.6	History Interface	28		

5.0	ADA	APTATION REQUIREMENTS	29
	5.1	Security and Privacy	
	5.2	Design Constraints	
	5.3	Data Integration	
	5.4	Performance	
6.0	FIIT	URE DESIGN	31
0.0	6.1	Update/Archive Organizations	
	6.2	Maintain Organization Affiliations	
	6.3	Update/Archive Contacts	
	6.4	Maintain Contact Affiliations	
	6.5	Maintain SIC Codes	
	6.6	Maintain NAICS Codes	
	0.0	Trainain I v Hoo Codes	
7.0	ERR	OR HANDLING REQUIREMENTS	34
APP	ENDIX	A Physical Data Model Data Definition Language (DDL)	
		EXHIBITS	
Exhi	bit 1.]	Envirofacts Data Flow	10
Exhi	bit 2. 1	Main Menu	12
		Add New Program Record	
Exhi	bit 4.]	FII Application Home Page	17
		User Registration Form	
		Facility Information Query Form	

1.0 INTRODUCTION

This document specifies the design specifications for the Facility Identification Initiative (FII) application in Envirofacts. FII is a product of the Environmental Protection Agency's (EPA) Information Resources Management=s (IRM) Executive Steering Committee (ESC). The FII application development is a key element in the EPA=s initiatives to improve information management, including:

- Using information strategically to achieve the Agency=s mission.
- Using information to empower EPA=s partners.
- Establishing an integrated information infrastructure to support a comprehensive approach to environmental protection.
- Establishing a more effective organization for information resources management.

FII has been instrumental in re-engineering the Facility Index System (FINDS) to meet the need to Aestablish an integrated information infrastructure. The FII application is being developed as a re-engineered FINDS, a component of Envirofacts in an Oracle relational environment, at the request of the Office of Information Resources Management (OIRM), Enterprise Information Management Division (EIMD), under Delivery Order (DO) 91 of the Mission Oriented Systems Engineering Support (MOSES) contract at the EPA Systems Development Center (SDC).

FII goals relevant to this system are:

- To obtain and maintain an accurate set of uniform identification information about facilities and other place-based objects.
- To establish an infrastructure to manage this identification information in a manner that efficiently supports data linkage capabilities.
- To provide a means of access to this information by all interested parties and to establish linkages to more detailed environmental data.

The One Stop Reporting Program, a major influence in the development of the FII application, is a reinvention program designed to streamline environmental reporting for the regulated community. The program also provides access to integrated environmental information, and improves public access to meaningful information about both the industry and the regulator's performance.

1.1 Background

FINDS functions as a centralized IBM mainframe ADABAS database of facilities that are regulated or monitored by EPA programs. FINDS maintains a set of linkages that allow the FINDS identification number to relate data for the same facility in multiple program office systems. FII development incorporates the redesign of the FINDS database as part of the Envirofacts Warehouse in an Oracle database environment.

1.2 Purpose

The purpose of this design document is to identify the specifications to be used in developing the FII application to function as the source for EPA=s integrated facility identification and locational holdings.

1.3 Scope

The scope of this design document includes all requirements, data, processing, reporting, maintenance, and security, as defined for the FII application Operations and Maintenance (O&M) capability and in support of the FII data in Envirofacts.

1.4 Identification

This document serves as the design specification for the FII application O&M capability and in support of the FII data in Envirofacts. This work is being conducted by the FII Development Team under DO 91 at the SDC.

1.5 System Overview

FII Version 1.0 is currently being developed as a production system that includes program office data from FINDS and the functionality of FINDS that supports integration of EPA data. On March 31, 1998, prior to the full implementation of the FII application, some of the supporting data structures were implemented in Envirofacts to support queries of current Envirofacts FINDS data. By September 30, 1998, the FII application will become fully functional and all facility identification data will be installed in the FII application, all functionality for managing that data will be implemented, and the mainframe FINDS will cease to operate.

The functions of FINDS that relate to the access of Dun and Bradstreet (D&B) data will be implemented in Envirofacts on the EPA Intranet, where access is restricted. These D&B functions will be accessible through Envirofacts queries, but not as part of the FII application.

During the FII application development and testing period, FINDS continues to serve the needs of EPA and the public, while operating on the EPA IBM mainframe computer at Research Triangle Park (RTP), North Carolina.

FII data will be available to all Envirofacts users as its central facility identification and locational component, and as the source of integrated access to environmental data. Oracle is the primary database component of the EPA Information Technology Architecture (ITA) for the World Wide Web (WWW)-based applications and support. Envirofacts has continued to be developed to complement and be consistent with the Agency-s information management data architecture, using all applicable EPA information management standards. The Envirofacts database is available to Agency personnel on EPA internal servers. A wide variety of non-Agency users (e.g., industry, environmental groups, and the general public) can access the database through the WWW on the EPA public access server.

The development environment for the FII application (i.e., the Oracle Relational Database Management System [RDBMS], using the UNIX operating system) is consistent with the hardware, software, and communications environment for Envirofacts. The use of the Oracle RDBMS also satisfies the Federal Data Processing standard, which requires that all relational databases be based on the Structured Query Language (SQL). FII application implementation in the Envirofacts environment will provide timely access to facility identification information and direct integration of Agency data for program office data implemented in Envirofacts.

The re-engineering of FINDS into the FII application will include the following strategic capabilities that did not exist in the mainframe FINDS system:

- Search/resolution support for Complex Facilities (e.g., water systems) when specified.
- Support for future state data sharing.
- Support for data entry and resolution of North American Industry Classification System (NAICS) Codes.
- Extended, flexible facility searches by contact and organization name.
- Access to program office-maintained contact, organization, and mailing address information.
- Interface tools for data analysis (e.g., multiple browsers, multiple searches).
- Public access to integrated EPA facility data.
- A variety of access methods supporting Web-based reporting.

1.6 Assumptions

Assumptions pertaining to the FII application design specification include:

- Two separate database systems will be maintained. The FII application O&M database will be incorporated into the Envirofacts environment and be accessed through the EPA Intranet. The search and retrieval of FII data will be supported as the facility component of Envirofacts and will be available for Internet-based public access.
- Facility identification numbers and their linkages to program office system identifiers from the existing FINDS will be used for the initial load of FINDS.
- On-going resolution of FII with facility data from states and program office systems will consist of two processes. The first process is resolution on a monthly basis for all program office systems included in Envirofacts. The second process is resolution of data extracts from program office systems, states, and other designated Agency data collections that are facility-based and not available as Envirofacts components. It is anticipated that EPA will make these non-Envirofacts files available on at least a semi-annual basis.
- The following external interfaces will be supported:
 - External files extracted from state facility systems and EPA environmental program office systems to support data maintenance transactions (i.e., adding, updating, and deleting rows)
 - Manual data maintenance, both for Headquarters staff and for designated state and regional representatives shall be supported through the Intranet.
 - Interfaces will be supported through the Internet for receipt of public comments and discrepancy reporting.
- Facility location and identification data for all participating states and program office systems will be contained in FII; a virtual master FII record will be created.
- The D&B data files will be available on the EPA Intranet for reference to facilities through the DUNS Number.

All relevant EPA and Federal standards for information management will be incorporated in FII, including:

- Federal and Agency standards for data, data format, and domains of reference data. Standards are currently being developed to provide uniform definitions and formats for commonly used data in Agency data systems. These standards are recorded in the Environmental Data Registry (EDR), including geopolitical data (i.e., country, state, country, and tribal lands), Standard Industrial Classification (SIC) and NAICS Codes, facility category and facility type, and metadata for spatial data.
- Locational Data Policy (LDP) standards as described through the Method, Accuracy, and Description (MAD) Codes implementation guidelines. FII will support interfaces with the Locational Reference Tables (LRT) for EPA-regulated and monitored facilities, and associated features.
- Federal and Agency standards for the computing infrastructure related to hardware, software, and telecommunications networks.

1.7 Constraints

The FII application is developed within the constraints of a variety of on-going EPA initiatives which relate to goals for the reinvention of government. Initiatives that affect the design and development are:

- Reinventing Environmental Information (REI) standards development, including data standards (e.g., standards for date and address representation), system development standards (e.g., standards for naming and defining data elements), and standard reference domains (e.g., geopolitical data and SIC Codes).
- The FII interim standard for facility identification, including the need for standard locational and identification data, and assignment of a Unique Identifier (UIN) to all facilities regulated by EPA.
- The One Stop Reporting Program=s demonstration of the feasibility of full-scale implementation of the basic elements for an effective environmental reporting and data management system, with emphasis on state level participation.

Issues that affect the implementation include:

- The inconsistent identification of facilities and other features of environmental concern in Agency program office systems.
- The multiplicity of hardware, software, and communications networks used within the Agency that inhibit data sharing.

1.8 User Community

The FII application serves the needs of several different types of users, through access to Envirofacts via the Intranet and Internet. The different types of users have been identified based on their role and needs:

- Federal EPA users such as Headquarters, enforcement officials, hazardous waste managers, regional offices, program offices, and program office system managers.
- State environmental agencies and state partners, who provide facility data, obtain UINs, and facilitate the use of UINs in state data that are provided to the Agency.
- Other Federal government agencies such as the Department of Transportation (DOT), United States Geological Survey (USGS), Federal Emergency Management Agency (FEMA), and Occupational Safety and Health Administration (OSHA).
- General public, such as community action committees and grass-roots organizations, environmental groups, individual companies, and industry groups.

2.0 REFERENCES

Requirements for the Re-engineering of FINDS: A Prototype Facility Registry System, SDC-0055-091-ER-6004, December 20, 1996.

FII Business Rules, Working Document, June 20, 1997.

Facility Index System (FINDS) 4.2 Physical Design Amended, SDC-0055-050-BS-3015A, May 15, 1995.

Updated Facility Index System (FINDS) Operational and Procedural Manual, SDC-0055-040-AS-6009, November 25, 1996.

Facility Index System (FINDS) User ₹ Manual, SDC-0055-040-DB-4013C, July 1996.

Facility Index System (FINDS) Phase 2 and Phase 3 Requirements Statement, SDC-0055-029-AM-2021A, September 8, 1993. Specifications for FINDS Development, Phases 2 and 3, SDC-0055-029-PJ-3004, December 16, 1993.

Recommended Data Elements for the Data Collection Form in Support of the Key Identifier Data Standards, SDC-0055-057-LF-4029, June 13, 1995.

Approach for Implementation of Corporate Tree Information to Support the Key Identifier Rule - Working Paper, SDC-0055-057-LF-4028B, June 26, 1995.

Unique Identification Number (UIN) for Identification of Place-Based Objects at the Environmental Protection Agency, SDC-0055-057-LF-5031A, June 24, 1996.

Envirofacts Database Description and Maintenance Procedures, SDC-0055-051-MA-5031, January 31, 1996.

Interim Final Recommendations, Facility Identification Initiative, December 15, 1997.

Environmental Data Registry Website, URL: http://www.epa.gov/edr/.

Facility Location and Identification Data Content Standard, Federal Geographic Data Committee (FGDC), Public Review Draft, December 1997.

Requirements Specification For The Facility Identification Initiative System (FIIS) SDC-0055-091-LF-7041, March 4, 1998.

3.0 SYSTEM DESCRIPTION

The FII application provides a registry of EPA-regulated facilities, monitored facilities, and other facilities of interest to the States. This registry will provide a repository of facility locational and identification data, which will enable integrated queries of the environmental data, and the ability to track environmental actions captured in program media data systems. In addition, the FII application provides for the capability for states to integrate state and national environmental data for regulated facilities.

The FII application will provide a UIN for these facilities. The UIN will support integrated search and retrieval of environmental data about a facility across program office systems by establishing linkages with program office system identifiers. The FII application will assist regulatory and enforcement actions by providing linkages to locational data (i.e., latitude, longitude, and associated metadata) and historical records that enable tracking of environmental activities by facility and responsible organizations. Envirofacts will provide access to corporate hierarchies that show parent and subsidiary companies, that is, D&B data files through the EPA Intranet.

3.1 System Operation

The FII application will provide a set of tools with the capability to perform integrated searches across facility-based program office systems contained in Envirofacts. These are planned to include the Aerometric Information Retrieval System Facility Subsystem (AIRS/AFS), the Biennial Reporting System (BRS), the Comprehensive Environmental Response, Compensation, and Liability Information System (CERCLIS), the Permit Compliance System (PCS), the Resource Conservation and Recovery Information System (RCRIS), the Toxics Release Inventory System (TRIS), and others as they become available (e.g., the Safe Drinking Water Information System [SDWIS]). FII contains locational and identification data from program office systems that are not contained in Envirofacts (e.g., Section Seven Tracking System [SSTS], Federal Facilities Information System [FFIS], National Compliance Database [NCDB], PCB Activity Database System/PCB-Handler Activity Data System [PADS], and Enforcement Docket System [DOCKET]). FII will also contain geographic address, mailing address, and industrial classification codes (i.e., SIC Code or NAICS Code).

The FII application includes active facilities (i.e., facilities for which program office systems currently collect and store environmental data), facilities of interest (i.e., places of environmental interest for which program office data does not yet exist), and inactive facilities (i.e., facilities that are no longer monitored) with linkage history to program office identifiers.

3.2 Equipment

The FII application in Envirofacts will operate in the production UNIX environment at RTP as part of the Envirofacts database server. Client machines accessing the FII application must have sufficient disk space and memory to load and run the FII application and reports. The minimum desired recommendation for Windows-based client machines is a Pentium 90 with 32 megabytes (MB) of Random Access Memory (RAM). FII application users are recommended to use Netscape Web Browser, which is an EPA standard to run the application, and an Internet Protocol (IP) address.

3.3 Support Software

The FII application provides online help on how to use different functions available in FII, such as how to add and maintain program office facilities, and how to perform manual resolution. FII application also provides a data dictionary and metadata references at every level of the FII application.

4.0 SOFTWARE PRODUCT DESCRIPTION

4.1 Data Requirements

The FII application will support the data elements that are identified by FII and proposed by the One Stop Reporting Program Initiative. The FII data requirements are captured in a logical data model, developed using the Oracle Designer/2000 Computer Aided Software Engineering (CASE) tool. Appendix A presents the Data Definition Language (DDL).

The FII application will capture date fields through Change File Processing and store all date fields with a four digit year to support Year 2000 compliance.

4.2 Interface Processes

The FII application interface, as shown in Exhibit 1, includes: Envirofacts program office system facility data, state and non-Envirofacts program office system facility data, data maintenance, and LRT data. Exhibit 1 presents the Envirofacts Data Flow as described in the following sections. Section 4.3.7.1 Resolution Process describes the Change File Processing or the Envirofacts data refresh procedure that will be used to delete, update, or insert data to the automated resolution process as described in Section 4.3.7.2. These processes provides the facility data to the FII application resident on the Intranet. Other Envirofacts change file processes will continue to provide scientific data to Envirofacts resident on the Intranet and Internet. Nightly updates will occur from the FII application resident on the Intranet to FII data in Envirofacts.

Data Stewards will provide user registration support, manual on-line data maintenance and resolution, and processing discrepancies and feedback.

4.2.1 Envirofacts Program Office Systems

The Envirofacts Change File Processing will capture changes to the program office data as scheduled; these changes will be incorporated into the FII application database through the automated resolution process. Facility data files that will be processed through a resolution process include: AIRS/AFS, BRS, CERCLIS 3, PCS, RCRIS, TRIS, and SDWIS.

4.2.2 States and Non-Envirofacts Program Office System Facility Data

External facility data file extracts shall be captured from sources outside the Envirofacts Warehouse, including program office system facility data and State facility data. Facility data extract files from states shall be obtained in a schedule from all One Stop Reporting states that maintain central facility data systems. Non-Envirofacts EPA program office system facility-based data extract files shall be obtained from EPA program office systems for FFIS, SSTS, NCDB,

PADS, and State data. It is anticipated that EPA will make these files available on at least a semi-annual basis.

The FII application shall support DOCKET, which carries data on legal cases and other program office data where a many-to-many relationship exists between facilities and cases. Non-Envirofacts EPA program office systems currently in FINDS that will not be included in the FII application are the Chemicals in Commerce Information System (CICIS), Contractor List, and Criminal Docket.

4.2.3 Data Maintenance

The FII application shall provide an interface, through Web pages, to capture and update facility data from headquarters representatives, EPA Regional and State Data Stewards, and authorized program office system Data Stewards (e.g., PADS, CERCLIS, and DOCKET).

• The FII application shall support data maintenance of a Complex Facility (e.g., airport, university, military base), Single Facility (e.g., dry cleaners, service station), and provide an index or pointer to the feature of a facility (e.g., pipe, stack), which is detailed in program office system data.

- When the FII application presents a data search option the user may choose a course of action as described in Section 4.3.5 Facility Search Components.
- The FII application will automatically capture the history of system transactions.
- The FII application provides a comment field to enable the user to manually enter appropriate information for a program office facility record.
- The FII application will use existing links AFINDS Numbers@from the FINDS mainframe to populate Facility_UIN. The FII application will not generate AFINDS Numbers@after the full implementation of FII in October.

4.2.4 Dun and Bradstreet Data

The D&B database will be implemented in Envirofacts on the EPA Intranet, where access will be restricted. The system will be accessible through Envirofacts Queries, but not as part of the FII application. EPA staff and designated contractor staff only will have complete access to D&B corporate information.

4.2.5 Locational Reference Tables

The LRT will provide latitude, longitude, and related metadata for facilities. LRT is being redesigned to store latitude/longitude and related (locational) data supplied by program systems, regional offices, and states which will be included in the FII application in Envirofacts. LRT will continue to process data only via batch transactions. FII will contain all LRT non-Spatial Data Option (SDO) tables and columns. LRT will process locational data via batch and online transactions within FII application. The batch transactions will process data supplied from any source including program systems, regional offices, and contractors, where the supplied data conforms to the LRT file format. Data that does not conform to the LRT file format will be rejected during the Envirofacts Change File Processing and returned to the data source.

Locational data will be compared to latitude-longitude values determined from the facility data corresponding to the location of the program system entity. Results of comparisons between locational data to the County and ZIP Code and provided measurement accuracy values will determine preferred sets of locational data for a program system entity.


4.3 Functional Components

The FII application provides an interface to support program facilities, organizations, contacts, mailing addresses, SIC Codes and NAICS Codes, user administration, and latitude/longitude data. In addition, the FII application provides search, reporting capability, and discrepancy processing.

To provide tracking of information about facilities and affiliated organizations, a unique identifier will be assigned to each organization, contact, and mailing address.

4.3.1 Facility Maintenance


The FII application provides data maintenance user capabilities as shown in Exhibit 2, to search for active facility information, generate standard facility reports, view facilities with incomplete data, view history of modified/archived facilities, add a facility, and change password.



4.3.1.1 Add A Facility

The FII application provides an interface to register new facilities. As shown in Exhibit 3 some data elements are required and must be entered in order to register a facility in FII. This interface performs an automated search of the FII database using the information entered for the facility to make sure that the facility being added does not exist. If a similar facility is being monitored by

other program systems this interface will display a candidate list of facilities with the following information: Facility UIN, Facility Name, Location Address, Program System ID, and Program System Acronym. Users can link the selected program record(s) to the existing facilities or add as a new facility.



In the FII application the Facility UIN will be generated for two different types of Agency systems, as follows:

Agency program systems that provide facility data for resolution through the Envirofacts refresh process as of October 1998, such as: TRIS, RCRIS, PCS, AIRS/AFS, CERCLIS 3, NCDB, SSTS, FFIS, PADS, STATE, Underground Injection Control (UIC), BRS, SDWIS. Reference Section 4.3.7.1 Resolution Process for details of this process.

• Agency systems such as DOCKET that are only interested in the Facility UIN generated by the FII application.

For Agency program systems that provide facility data for resolution through the Envirofacts refresh process as of October 1998, the following rules will be applied:

- If the System ID and Acronym are provided, the FII application generates the Facility UIN using this information and assigns the value of PENDING to the Program Facility Status. PENDING status indicates that no program system is currently monitoring the facility.
- If the System ID is not provided, the FII application will populate this field with the generated Facility UIN (e.g., CERCLIS currently uses the FINDS Number as their program system ID) and assigns the value of PENDING= to the Program Facility Status.

For Agency program systems such as DOCKET that are only interested in the Facility UIN generated by the FII application, the following rules will be applied when a new Facility UIN is generated:

- The FII application will concatenate the Docket Case Number and a system-generated sequence number (to resolve the many to many relationship of DOCKET cases and facilities) and assign this concatenated value to the System ID, and assign the value of >DOCKET=to the Acronym.
- Program Facility Status will be set to >ACTIVE=. This status indicates that at least on program system is monitoring the facility.

Note: Facilities assigned APending@value for more than 90 days will be deleted from FII and will be archived in the history file.

- Users can select and link to existing records from the list of the search result that matches
 the description of the new program record, otherwise the user can add the record as a new
 program record.
- Add New Program Record will prevent the addition of duplicate program records by examining the existence of the program record using the program system ID and acronym.
- Add New Program Record will examine the validity of data entered using the look-up tables to maintain referential integrity.
- Add New Program Record will populate parsed address, standardize name, and assign data quality to the program facility record.

- For new program records entered through the interface, users will be able to select the facility category of Single=or Complex= and enter any additional program facility data.
- A facility that is uniquely identified by name and location will be assigned a facility UIN, which is generated when the facility is registered in FII. The facility UIN will be the identifier used to establish linkages throughout the FII application. Add New Program Record will maintain the parent/child relationship (i.e. storing new facilities in both the FRS_FACILITY and FRS_PROGRAM_FACILITY tables).
- The facility UIN has 12 digits, the last of which is a check digit. UIN values will be generated using the algorithm described in Appendix D in *Facility Location and Identification Data Content Standard*, Federal Geographic Data Committee (FGDC), Public Review Draft, December 1997.

4.3.1.2 Update Facility

Facilities manually registered through FII can be updated using the FII application Update Program Record Web page as long as program systems have not reported their facility data through the Envirofacts Change File Processing. If the program system ID and acronym are known, the user can enter this information to retrieve the program record, or a more general search can be performed to identify the program record to be updated. The FII application Update Program Record Web page will be similar to the Add New Program Record Web page with the exception that the following fields will not be modifiable; Facility UIN, Program System ID and Acronym, Data Quality Code, Standardized Name, State, Region, and any other system generated data.

- Update Program Record will examine the validity of data entered using the look-up tables to maintain referential integrity.
- Update Program Record will populate parsed address, standardize name, and any other system generated field if necessary.

4.3.1.3 Archive Facility

Program records can be archived and stored in the history table. Facilities that were, but are not currently, associated with any program office system record will be assigned the status of "Inactive" and will be moved to the history file. Archive Program Record should maintain the parent/child relationship in the FII tables. In addition facilities registered in FII can be archived as long as program systems have not reported their facility data Apending facilities. Pending facilities more than 90 days will automatically be archived.

4.3.2 Core FII Data Maintenance

The FII application allows data stewards to update core data elements such as Contacts, Organization, Mailing Address, and SIC and NAICS Codes associated with a facility that is being registered in FII. See Sections 6.0 through 6.6 Future Design Requirements.

4.3.3 Relink/Move Facilities


The FII application Relink and Move function allow facilities that are linked incorrectly or considered to be a duplicate facility (i.e. identical facilities having two different UINs) to be relinked or moved to a different facility.

- For an incorrect facility link, the move function enables a program record identified by a UIN to be changed to an existing UIN or to a new UIN.
- For a duplicate facility, the move all function enables the user to move *all* the program records associated with each of the two UINs under the correct or desired UIN. The duplicate UIN is automatically archived as a result of the move *all* function.

For both instances, the incorrect facility link and the duplicate facility, the move function copies the program facility record being moved to the history table. The history record captures the user comments (i.e., the reason for move) and the facility UINs prior to and after the move in order to provide a trail for tracking the UIN. In addition, the facility UIN of the moved program system record is changed to the new UIN.

4.3.4 User Administration


Access to the FII application is restricted to registered FII users. As shown in Exhibit 4, in order to log-on into the FII application users must have a valid user ID and password. The FII application provides an interface for new user registration and user activation and maintenance to handle user administration.



Any EPA Intranet user can submit a registration form by entering the required information and identifying the access level needed such as region, state and program system. Only Data Stewards can verify user information and activate a user so the user may log- on.

4.3.4.1 New User Registration

The FII application, as shown in Exhibit 5, provides an interface for a new user to register. To register, a user must provide the following information: name, company name, mailing address, city, ZIP Code, state, title, phone number, fax number, userid and password, and E-mail address. A user can enter a userid (i.e., a minimum of 3 characters and a maximum of 8 characters) and a password (i.e., a minimum of 6 characters and a maximum of 8 characters). Then the user will submit a request for update access to program system records in the geographic and program office system specified on the access level request form.



The information must be verified by primary Data Stewards and the user will be notified when the entered userid and password is activated through the E-mail address provided during new user registration.

4.3.4.2 User Activation/Maintenance

FII will provide an interface so that the primary Data Stewards can identify individuals requesting access. This interface should allow primary Data Stewards to view and update the registration tables once users have registered. The interface will also allow individual users to change passwords or update contact information.


- The FII application will provide an interface to primary Data Stewards to enable/disable users, reset passwords, change user access, and delete obsolete users.
- The FII application will allow primary Data Stewards to assign users to categories and limit data administration or data access levels (e.g., enable data entry for DOCKET users) by region and/or state and program office, or other basis.

• When a user has been activated or de-activated, the user will be notified by the E-mail address provided during new user registration.

4.3.5 Facility Search Components

The facility search interface as shown in Exhibit 6 allows users to search the FII database for program facility information. Facility searches can be conducted using multiple search criteria such as: search using geographic information, facility name, contact or organization information, SIC or NAICS Codes. When searching for information on a specific facility, single criteria search can be performed using the facility UIN, DUNS number, or System ID and Acronym as the search criteria. The facility search result will display the facility UIN, program system acronym and ID, program facility name, and the location of the program facility.

- Single criteria searches will be limited to:
 - EPA ID.
 - DUNS Number.
 - System ID and Acronym.
- Multiple criteria searches, including:
 - States in combination with cities or counties.
 - Program office system identifier in combination with program office system acronym.
 - Region in combination with states and cities or counties.
 - ZIP Code in combination with facility name.
 - Street address in combination with state or ZIP Code.
 - Street address in combination with city or state or ZIP Code.
 - City or county in combination with state.
 - City or county in combination with state and facility name.
 - Facility name in combination with state and contact=s last name.
 - Facility name in combination with state and organization name.
- The search interface provides users with a list of permitted values for applicable fields such as state, SIC and NAICS Codes, and EPA regions.
- The FII search interface look-up table listing counties, cities, and ZIP Code associated with a state will be part of the future requirements.



- Facility name searches provide four matching options: Begins With, Exact Name, Sounds Like Name, and Containing Characters.
- Searches that include state, county, and city allow up to five states and six cities or counties.
- The facility search result provides a list of all program office facility records where the search criteria is satisfied, organized by program facility name. Users can select a program system facility record from the list to view the facility detail information and the affiliated data (i.e, contact, organization, SIC/NAICS Codes, latitude/longitude, and mailing address).
- The search interface provides the capability to search for facilities being monitored by a specific program office, or multiple program office; the default is "All."

• UIN values will be displayed as Annnn-nnnne where the first set of digits are zero-filled to display twelve digits, and the twelfth digit is the generated check digit.

4.3.6 Reporting Capability

The FII application provides an interface to replicate FINDS reports such as Standard Facility Reports, System Administration Reports, and Summary Statistical Reports. The reports include:

- Facility Reports.
 - Facility Summary Report.
 - Facility Detail Report.
 - Facility Cross Reference Report.
- System Administration Reports.
 - Year-to-Date User Information.
 - User Information.
 - Monthly Activity Reports.
 - Merge Notification Report.
 - Resolution Status Report.
 - Resolution Activity Report.
 - Delete/Merge Notices.
 - Analyst Activity Report.
 - Facility Count Report.
 - Audit Trail Report.
 - Activity Report.
- Linkage Quality Report.
- Summary Statistic Reports.
 - All regions.
 - One region.
 - One state.
 - One city/state.
 - One county/state.
 - One zip code.

4.3.7 Resolution of State and Program Office System Facility Data

The FII application data resolution is the set of processes (both Data Steward-guided and automated) that link state and program office extract data to existing FII facility records. The data loading or refresh procedures are considered necessary prerequisites to any resolution

activity. All new program system and state records will be assigned UINs and will be stored in FII, regardless of the completeness and accuracy of the data.

The FII application performs a similar but improved data resolution process as the production mainframe FINDS Version 4.2.11, which includes data searches to determine potential linkages, and construction of program office system record lists that are potential linkage candidates. Data will be maintained through both manual and automated resolution processes. The automated process includes manual verification where automated processes cannot complete data maintenance transactions.

4.3.7.1 Resolution Process

After the initial load of state and program system facility data, which includes pulling FINDS program system records and the linkages for the active facilities in FINDS, the Envirofacts data refresh procedure will be used to maintain the FII facility data. This process uses the Change File Processing which consists of three data types, each of which has a corresponding file type: an Insert File which contains new data, a Delete File which contains data that has been deleted, and an Update File which contains data that has been changed. Data contained in these files are applied to the corresponding resolution tables for each program system, so that the data for each table is concurrent with the most recent extract that resides on the EPA IBM mainframe computer.

The Envirofacts Change File Processing and the FII resolution subsystem is a collection of procedures that are accessed manually; they reside on the EPA IBM mainframe and on the UNIX server resident at Research Triangle Park (RTP). Envirofacts will provide change files for all facility based program systems that are currently in the FINDS database.

- The existing Envirofacts extract programs will be modified to generate change files for the program facility data in the format of the FII resolution tables. Other change files that currently are being generated for Envirofacts (i.e., scientific data) will continue to be generated and maintained for use in Envirofacts.
- The formatting of the program system facility data to the resolution tables should include derivation of State_Code, State_Name, County_Name, and EPA_Region_Code.
- Some states (i.e., \forall L= and \forall XY=) that maintain their state-specific facility data through FINDS on-line application, may continue to maintain and clean up their state specific facility data through the FII application.

- New extract programs will be developed to extract SDWIS and BRS data and generate change files in the format of the FII resolution tables.
- The existing pre-formatted program system extract files that are currently obtained by FINDS from NCDB, PADS, SSTS, FFIS, STATE, and UIC will be formatted to generate change files in the format of the FII resolution tables.
- The generated change files for each program system must have only one Insert, one Update, and one Delete file for each of the resolution tables; each program system will contain a maximum of 12 change files for program facility. Insert file examples include:

PSDB.FII.PCS.INSERT.FACILITY.<month> PSDB.FII.PCS.INSERT.CONTACT.<month> PSDB.FII.PCS.INSERT.ORG.<month> PSDB.FII.PCS.INSERT.SIC.<month>

• Prior to applying the Inserts and Updates to the FII database, FII back-end processing will populate parsed address fields, soundex fields and the standardized name.

4.3.7.2 Automated Resolution

The FII application automated resolution is a back-end processing (i.e., a set of PL/SQL routines) that will use the data in the resolution tables and apply the data to the corresponding FII tables. This process first applies the delete files to the FII database. In this process the program system ID and program system Acronym from the resolution tables are used to archive the program system records from the FII database. A copy of this record will be stored in the corresponding history table and the status will be changed to inactive.

The FII automated resolution will use the following logic in reconciling new program system records identified in the Envirofacts Change File Processing:

The automated resolution will compare the facility name and address in the resolution table to the FII database, if potential candidates found and the System ID and Acronym are the same that record will be updated in the FII database with the information from the resolution table and a copy of the old record will be placed into the history table prior to update. If the System ID and Acronym doesn=t match but facility name and address matches, the new record will be assigned the same EPA ID. If the name and address do not match, then the automated resolution will assign a new EPA ID and flags this record for manual linkage. The automated resolution will change the Program record=s Status from >PENDING=to >ACTIVE=.

- The potential candidate list is based on the weighting algorithm score which is based on the number of data elements matched with a 75% or more score. The automated resolution will change the program status from *PENDING= to *ACTIVE=.
- The automated resolution will use the System ID and the Acronym from the resolution tables for records flagged as update and the corresponding record in the database. A copy of the original record will be stored in the history table.
- FII identifies and maintains a "virtual" master record that will be the preferred state or program office system record for a facility. The priority order for identification of the virtual master record is as follows:
 - 1. State (i.e., Facility identified by the state).
 - 2. TRIS.
 - 3. RCRIS Treatment, Storage, and Disposal.
 - 4. PCS Major.
 - 5. AIRS Major.
 - 4. Superfund NPL (National Priority List (NPL) facility as identified by CERCLIS).
 - 5. RCRIS Large Quantity Generator/Small Quantity Generator.
 - 6. PCS Minor.
 - 6. AIRS Minor.
 - 7. CERCLIS (Any facility not identified on the NPL by CERCLIS).

4.3.7.3 Manual Resolution

States and data stewards will use the manual resolution to clean up and improve their facility linkage quality. During this process the program facility records that are flagged as manual linkage (i.e., AM@) will be compared with other program system records and a list of potential candidates will be provided to allow states or Data Stewards to visually review and decide the correct linkage. The candidate list will be ranked based on the occurrence of similar locational data matches with the records that are flagged for manual resolution.

- Searches will be conducted to retrieve a list of potential candidates from the active program office facility tables and the history tables.
- An interface will be provided to link new program facilities to existing facilities in FII.
- Manual resolution will reset the processing status flag once the user has confirmed the linkage.

- Manual resolution allows program records or facilities that are linked incorrectly to be re-assigned (i.e., relinked or moved).
- The resolution tables must be truncated prior to loading of the next set of change files.

4.3.7.4 Data Quality Code and Feedback Processing

The data quality code process is initiated after the automated resolution completes processing the program system records and establishing proper linkages. The data quality code is assigned based on the completeness, consistency, and validity of the facility data (e.g. facility name, location address, city, state, county and ZIP Code). A copy of the program facility records with a data quality code that indicates missing, invalid, or incomplete will be stored in the feedback tables for processing. The following assumptions will be made in assigning the data quality code:

- If the facility name is null/missing, the record is not processed any further and is marked with an invalid data quality code.
- If the state is missing or invalid, the record is not processed and is marked with an invalid data quality code.
- The records are processed if they contain facility name and valid state code and any combination of city or county or postal code.
- The assignment of the data quality code will not use the cross reference check for the facility name and street address fields against the United State Postal Services (USPS) street address data.
- A validation check will occur on the facility name and street address fields against an Aanomalies/abnormals@table (i.e., checking for occurrences of words such as AMISSING@ or AUNKNOWN@in either facility name or street address field).
- A cross reference check will occur for certain combinations of the state, postal code, city and county fields against the USPS data.
- Data sources (e.g., program offices, states) will be notified of facility records with data quality codes that indicate missing or invalid data.

Program system records with missing or invalid facility name, missing or invalid street address, missing or invalid state code will automatically be placed in the FRS FEEDBACK table.

The FII application provides an interface to AView Facilities with Incomplete Data@. This interface allows users to search the FRS_PROGRAM_FACILITY table based on the acronym, state, EPA region and the data quality code. From this interface data stewards can generate reports that are down-loadable or view the search result on the Web browser. This interface also displays how many times a program record with invalid data was placed into the feedback tables. Using this interface data stewards can place a copy of the program record into the feedback table. The feedback files contain program office data that is considered of poor or questionable data quality as defined by the data quality code.

The FRS_FEEDBACK table specifies missing or inconsistent information about a program system=s main data (i.e., facility name, location address, city, county, state, zip), and information about when a record is put in feedback and whether it has been sent back to its respective program system office for correction. FII will provide an interface to review and process records stored in the feedback table.

4.4 Data Validation

The FII application provides validation and edit checks to validate data entered on the maintenance Web pages. The FII application contains a repository of look-up information used to validate information. The look-up tables are used to validate locational information such as State Code, Zip Code, County Code, and Name. The FII application will also maintain a look-up table that contains the following:

- Data Quality Codes identified by code_type of >DATAQUALITYCODE=.
- Reason Code identified by code type >RSN CODE=.
- SIC/NAICS Codes identified by code_type >SIC CODE=/ >NAICS CODE=.
- Hydrologic Unit Code (HUC) identified by code_type >HUC CODE=.
- Affiliation Type identified by code_type >AFF CODE=.
- User Category identified by code_type of >USER CATEGORY=.

Data element validation methods are as follows:

- The facility UIN will be validated based on the check digit.
- Country, state, county, ZIP Code, city name, facility type, and SIC Codes will be validated as existing in the standard domains provided as look-up tables.
- Address elements will be validated for consistency across data fields (e.g., validating that a county is located in the state associated with the record).

4.5 Discrepancy Reporting and Processing

The general public can access and review the FII application data through Envirofacts. Upon reviewing the program office data, if they identify discrepancies (e.g., inconsistencies) in the program office data they will be able to submit comments to the responsible parties through an interface provided in Envirofacts. The option to submit a discrepancy will be available at the Envirofacts Web pages where the detailed information about a program office record is displayed. Envirofacts will capture and store discrepancies in different FII tables based on the type of discrepancy (i.e., Contact, Organization, Facility, SIC or NAICS Codes).

In order to process discrepancies in the FII application, the Envirofacts discrepancy interface should include a comment area to supplement changes with commentary text provided. Envirofacts must capture as much information as possible regarding the reported discrepancies. The reported discrepancies that contains user recommended values for each field must be stored in the corresponding FII discrepancy tables. In order to process discrepancies in FII and send a correspondence to inform the individual that reported the discrepancy, some information such as: individual=s name, organization, phone number, E-mail address will be required.

- Program system facility data-related discrepancies and the user recommended values must be stored in the FRS_PGM_FACILITY_DSCRP and at minimum the following data elements must be populated:
 - FACILITY_UIN
 - PGM SYS ACRNM
 - PGM SYS ID
 - STATE CODE
 - REPORTER COMMENT
 - TIMESTAMP
- Program system organization data discrepancies must be stored in the FRS_ORGANIZATION_DSCRP and at minimum the following data elements must be populated:
 - ORGANIZATION UIN
 - PGM SYS ACRNM
 - PGM_SYS_ID
 - AFFILIATION_TYPE
 - REPORTER COMMENT
 - TIMESTAMP

- Program system contact data discrepancies must be stored in the FRS_CONTACT_DSCRP and at minimum the following data elements must be populated:
 - CONTACT_UIN
 - PGM SYS ACRNM
 - PGM_SYS_ID
 - AFFILIATION TYPE
 - REPORTER_COMMENT
 - TIMESTAMP
- Program system SIC and NAICS Code data discrepancies must be stored in the FRS_SIC_NAIC_DSCRP and at minimum the following data elements must be populated:
 - SIC CODE
 - NAIC CODE
 - PGM SYS ACRNM
 - PGM_SYS_ID
 - REPORTER COMMENT
 - TIMESTAMP

The FII application will provide an interface to review and process discrepancies. Data Stewards can view, generate reports, and update and monitoring status of each discrepancy through this interface.

4.6 History Interface

The FII application provides an interface to the history tables to provide integrated information on changes to the FII database. Changes to the database due to automated resolution, manual resolution, facility relink, or move processing will be captured in the appropriate history tables.

The FII application will maintain Ahistory@information identifying all of the changes to the program facility data. When changes are made to the facility data (e.g. facility name, organization, or mailing address) a history record will be created with an exact copy of the previous record, a comment as to the change made, the author of the change which will be a standard acronym if the change was due to an automated process, and the date and time of the change. The recorded history information will enable the restoration of the unchanged information, to provide the ability to maintain an audit trail of changes. FII will not maintain a history of contact changes.

5.0 ADAPTATION REQUIREMENTS

The adaptation requirements will include security and privacy, design constraints, data integration, and performance.

5.1 Security and Privacy

The FII application will keep track of a registered set of users. Database and application access will be restricted based on user type. Users will be registered through the front-end application, at which time users will request the type and level of access needed. The FII application will not enable registered users to log-on with their registered name until official documentation has been received from the user's organization, authenticating the level of privilege requested. Other federal agencies and the general public will access the FII data through the Envirofacts database. The system will provide security features that define access limits for various user categories.

- EPA regions and states will have registered Data Stewards. A Data Steward will be responsible for entry, deletion, creation, and update of registry data (i.e., program office facility data, contact and organization, mailing address, SIC/NAICS information) to which access is categorized by program office system and state or by program office system and region.
- All Data Stewards will register, through the FII interface, to receive a protected user ID and password, and to request data access privileges.
- Each region/state will have primary and alternate Data Stewards responsible for communication and authorization.
- The region/state Primary Facility Identification Data Steward will be responsible for user authorization for the assigned region/state. These responsibilities include the creation, modification, and update of the user profile structure, and performing related administration capabilities.
- The region/state Primary Facility Identification Data Steward will be responsible for maintaining accurate and up-to-date E-mail addresses and authorization listing of Data Stewards within their geographic location.
- Data Stewards will be granted a range of system privileges by the Primary Facility Identification Data Steward in the State or Regional Office.
- In states with Data Stewards, the State Data Stewards will have ultimate responsibilities within their authorized program office systems.
- Regional Data Stewards will have responsibility and authority in those geographic areas

where no State Data Steward is authorized.

• A small group of supervisory users or Headquarters Data Stewards will exist who retain access to the entire FII application and database. A Headquarters Data Steward will perform user authorization for all Region/State Primary Facility Identification Data Stewards, and possess all administration capabilities. A Headquarters Data Steward will be able to perform all functions of a Regional/State Data Steward.

5.2 Design Constraints

The FII application is being developed using Oracle Designer 2000 to generate individual modules. In order to meet the requirements, the generated modules require additional customized code. The customized code will need to be reviewed for updates as necessary with each subsequent release in Envirofacts.

5.3 Data Integration

- Facilities to be converted to FII from FINDS will be assigned the Asingle facility@category. Some of the SDWIS public water systems may be assigned the Acomplex facility@category as long as these water systems follow the FII business rules defined for a complex facility, and the component SDWIS facilities will be assigned the Asingle facility@category.
- As the FII application becomes more fully developed in the future, other "complex facility" types will be identified (e.g., military installations and airport installations), and some features (e.g., CERCLIS waste sites and STORET monitoring stations) might be identified as "feature."
- The FII application will support program office systems (e.g., DOCKET) where a many-to-many relationship exists between the facility and system identifier.

5.4 Performance

The FII application will ensure that interactive search results are returned in 3 to 5 seconds. The time will depend upon network traffic, hardware speed, and user-network interface. In general, complex searches and searches with multiple selection criteria and complicated reporting will take longer to complete.

6.0 FUTURE DESIGN REQUIREMENTS

The FII application Version 1.0 will be designed to manage information and provide linkages across a broad variety of facilities, including complex facilities (e.g., installations and networks), and features that are sub-entities of facilities (e.g., smoke stacks and discharge pipes). Future capabilities may include features that are not facility-related, but are of interest to EPA (e.g., hazardous waste sites and monitoring stations), and permitted sites where activities are planned but not currently established. The following requirements will be reviewed for implementation after September 30, 1998:

- Every facility will be associated with a category name that indicates its size and complexity. Manual addition of complex facilities in FII will be implemented after September.
- A new identifier will be created when the type of facility and location changes (including changes that increase or decrease the size of the property on which the facility is located).
- Changes to the facility type and generation of a new facility UIN.
- Generation and assignment of location UIN, which would enable tracking the changes at a location.
- The FII application will assign each location a UIN. The UIN will be generated using the same algorithm as is used to generate UINs for facilities.
- Each location may be associated with more than one facility.
- A facility will always be associated with exactly one location.
- When the last facility at a location is deleted, the location record is moved to location history (records in history are never deleted).
- When data about a location are changed and that data change does not indicate a change to the place identified (e.g., when the street name is changed or the USPS changes the ZIP Code), the location record is copied to the history file; the location UIN does not change.
- The FII application will maintain facility data with an interface to update and delete an interface to add, update, delete organization, contact, and SIC and NAICS Code.
- The FII search interface look-up table listing counties, cities, and ZIP Code associated with a state.

Sections 6.1 through Section 6.6 are additional future requirements that will be implemented after September, 1998.

6.1 Update/Archive Organizations

- The organization search allows users to search for organization records using Organization Name, DUNS Company Number, or the combination of both.
- Users can use partial name searches by entering partial name followed by % (i.e., stan%).
- From the organization search results users can select the organization record to be updated or archived.
- The update organization will store a copy of the organization record into the history table prior to the update.
- Organization records archived will be moved to the history table.
- When the organization information for a program record is updated and the same organization is affiliated with other program facilities, their organization information will be updated.

6.2 Maintain Organization Affiliations

- The Maintain Organization interface allows users to change the affiliation of an organization (i.e., from >OWNER= to >OPERATOR=).
- This interface allows users to remove/archive organization affiliations from a program facility.
- When the last association with an organization is removed, the organization record will be kept for a period of six months prior to being archived.
- The Maintain Organization interface allows users to add a new organization and affiliate it with a program facility. When adding new organization records users are required to enter Name, Mailing Address, State, and Affiliation Type.
- The FII application Maintain Affiliation will provide a link to update/archive organizations information.

6.3 Update/Archive Contacts

- The contact search allows users to search for contact records using Contact Name.
- Users can use partial name searches by entering partial name followed by % (i.e., brown%).
- From the contact search results the user can select the contact record to be updated or archived.
- When contact information for a program record is updated and the same contact is affiliated with other program records, the contact information will be updated too.

6.4 Maintain Contact Affiliations

- The maintain contact affiliation Web page allows users to change the affiliation of the contact to a program system (i.e., from >OWNER= to >OPERATOR=).
- Users are provided the capability to add a new contact record and affiliate it with a program record. When adding new contact records, users are required to enter Name, Mailing Address, State, and Affiliation Type.
- Users are provided the capability to update contact information for a program record.
- Users are provided the capability to remove/archive contact affiliations from a program record.
- A link will be provided to update/archive contact information from the maintain contact affiliation Web page.

6.5 Maintain SIC Codes

- Users are provided the capability to add new SIC Codes or archive existing SIC Codes associated with a program facility. Users can select SIC Code from the list of SIC Codes and their descriptions that are available as a look-up table.
- Users are provided the capability to indicate if a SIC Code associated with a program record is the primary SIC Code or not.

6.6 Maintain NAICS Codes

- Users are provided the capability to add new NAICS Codes or archive existing NAICS
 Codes associated with a program facility. Users can select NAICS Code from the list of
 NAICS Codes and their descriptions that are available as a look-up table.
- Users are provided the capability to indicate if a NAICS Code associated with a program facility is the primary NAICS Code or not.

7.0 ERROR HANDLING REQUIREMENTS

- The FII application will capture and store all Oracle errors in the FII application error tables.
- The FII application will translate cryptic Oracle error messages and display standard FII
 error messages.. These error messages capture the userid and the module where the error
 occurred.

APPENDIX A

Physical Data Model Data Definition Language (DDL)

CREATE TABLE FAC_LINKS (
PARENT_FACILITY_UIN	VARCHAR2(12) NOT	NULL,	
CHILD_FACILITY_UIN	VARCHAR2(12) VARCHAR2(12)	,	
FLAG	VARCHAR2(12) VARCHAR2(2)	,	
TABLESPACE D_FRS3	VARCHAR2(2)	NOLL)	
PCTFREE 10 PCTUSED 40			
STORAGE(INITIAL 532480 NEXT 8192 P	CTINCDE A SE (1)		
/ STORAGE(INITIAL 332460 NEXT 6192 F	CTINCKEASE 0)		
CREATE TABLE FRS_ACCESS_REGISTI	OV (
	•	NULL,	
USER ID	VARCHAR2(15)	,	
EPA_REGION_CODE	NUMBER(2,0)		
STATE_CODE	` ' '	NULL,	
_	CHAR(2)		
PGM_SYS_ACRNM	VARCHAR2(15)		
RECIPIENT_FLAG	CHAR(1)	,	
PRIME_FLAG	CHAR(1)	NULL)	
TABLESPACE D_FRS3			
PCTFREE 10 PCTUSED 40	CONTRACT (ACT 0)		
STORAGE(INITIAL 532480 NEXT 8192 P	CTINCREASE 0)		
CREATE TABLE FRS_CODE_DESCRIPT	`		
CODE_TYPE	VARCHAR2(20)		
CODE_VALUE	VARCHAR2(25)	,	
CODE_DESCRIPTION	VARCHAR2(120)	NOT NULL)	
TABLESPACE D_FRS3			
PCTFREE 10 PCTUSED 40			
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)			
/			
CREATE TABLE FRS_CONTACT (
CONTACT_UIN	NUMBER(12,0)	NOT NULL,	
FULL_NAME	VARCHAR2(50)	NULL,	
LAST_NAME	VARCHAR2(30)	NOT NULL,	
SOUNDEX_LAST_NAME	VARCHAR2(4)	NULL,	
TITLE	VARCHAR2(30)	NULL,	
EMAIL_ADDRESS	VARCHAR2(120)	NULL,	
OFFICE_PHONE	VARCHAR2(30)	NULL,	
HOME_PHONE	VARCHAR2(30)	NULL,	
FAX_PHONE	VARCHAR2(30)	NULL,	
MOBILE_PHONE	VARCHAR2(30)	NULL,	
USER_ID	VARCHAR2(15)	NOT NULL,	

```
SOURCE
                                     VARCHAR2(10)
                                                     NOT NULL.
                                                     NOT NULL,
TIMESTAMP
                                     DATE
PGM_SYS_ACRNM
                                     VARCHAR2(15)
                                                     NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 13107200 NEXT 442368 PCTINCREASE 0)
CREATE TABLE FRS CONTACT AFFILIATION (
CONTACT_UIN
                                     NUMBER(12,0)
                                                     NOT NULL,
PGM SYS ID
                                     VARCHAR2(30)
                                                     NOT NULL,
PGM_SYS_ACRNM
                                     VARCHAR2(15)
                                                     NOT NULL,
MAIL_UIN
                                     NUMBER(12,0)
                                                     NULL,
AFFILIATION TYPE
                                     VARCHAR2(25)
                                                     NOT NULL,
TIMESTAMP
                                     DATE
                                                     NOT NULL,
USER ID
                                     VARCHAR2(15)
                                                     NOT NULL,
SOURCE
                                     VARCHAR2(10)
                                                     NOT NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 16424960 NEXT 499712 PCTINCREASE 0)
CREATE TABLE FRS_CONTACT_DSCRP (
CONTACT UIN
                                                     NOT NULL,
                                     NUMBER(12,0)
FULL_NAME
                                     VARCHAR2(50)
                                                     NULL,
LAST NAME
                                                     NOT NULL,
                                     VARCHAR2(30)
                                                     NULL,
TITLE
                                     VARCHAR2(30)
                                                     NULL,
EMAIL ADDRESS
                                     VARCHAR2(120)
PGM_SYS_ACRNM
                                                     NULL,
                                     VARCHAR2(15)
PGM_SYS_ID
                                     VARCHAR2(30)
                                                     NULL,
                                                     NOT NULL,
AFFILIATION_TYPE
                                     VARCHAR2(25)
OFFICE_PHONE
                                                     NULL,
                                     VARCHAR2(30)
HOME_PHONE
                                     VARCHAR2(30)
                                                     NULL,
FAX PHONE
                                     VARCHAR2(30)
                                                     NULL,
MOBILE PHONE
                                     VARCHAR2(30)
                                                     NULL.
MAIL UIN
                                     NUMBER(12,0)
                                                     NULL.
DELIVERY POINT
                                     VARCHAR2(50)
                                                     NULL,
SUPPLEMENTAL_ADDRESS
                                                     NULL,
                                     VARCHAR2(30)
CITY_NAME
                                     VARCHAR2(30)
                                                     NULL,
STATE CODE
                                                     NULL,
                                     CHAR(2)
STATE NAME
                                     VARCHAR2(35)
                                                     NULL,
POSTAL CODE
                                     VARCHAR2(14)
                                                     NULL,
COUNTRY NAME
                               VARCHAR2(44)
                                               NULL.
REPORTER_USER ID
                                     VARCHAR2(15)
                                                     NOT NULL,
```

TIMESTAMP REPORTER_COMMENT	DATE VARCHAR2(120)	NOT NULL, NULL,
RECIPIENT_USER_ID	VARCHAR2(15)	NULL,
NOTIFICATION_DATE	DATE	NULL)
TABLESPACE D_FRS3		
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 8192 P	CTINCREASE 0)	
CREATE TABLE FRS_DOCKET_FACILIT		NOTATI
PGM_SYS_ID	VARCHAR2(30)	NOT NULL,
PGM_SYS_ACRNM	VARCHAR2(15)	*
DOCKET_CASE_NUMBER	VARCHAR2(30)	NOT NULL)
TABLESPACE D_FRS3		
PCTFREE 10 PCTUSED 40	CTINICDE A SE (1)	
STORAGE(INITIAL 532480 NEXT 8192 Po	CTINCREASE 0)	
CREATE TABLE FRS_ERROR (
ERROR TEXT	VARCHAR2(160)	NOT NULL,
ERROR_DATE	DATE	NOT NULL)
TABLESPACE D FRS3	21112	1(011(022)
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 8192 P	CTINCREASE 0)	
/	,	
CREATE TABLE FRS_ERROR_MSGS (
ERROR_MSG_NUM	NUMBER(12,0)	NOT NULL,
ERROR_MSG_TXT	VARCHAR2(240) NOT	NULL)
TABLESPACE D_FRS3		
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 8192 P	CTINCREASE 0)	
/		
CREATE TABLE FRS_FACILITY (
FACILITY_UIN	VARCHAR2(12)	NOT NULL,
FINDS_ID	VARCHAR2(12)	NULL,
FACILITY_CATEGORY	VARCHAR2(30)	NOT NULL,
MONITORING_STATUS	VARCHAR2(20)	NOT NULL,
ARCHIVE_DATE	DATE	NULL,
USER_ID	VARCHAR2(15)	NOT NULL,
TIMESTAMP	DATE	NOT NULL,
SOURCE USER COMMENT	VARCHAR2(10)	NOT NULL,
USER_COMMENT	VARCHAR2(240)	NULL)
TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40		
TOTTALE TO FOTUSED 40		

		July 2
STORAGE(INITIAL 46612480 NEXT 5439488 Pe	CTINCREASE 0)	
CREATE TABLE FRS_FACILITY_CTGRY (FAC_CATGRY CATGRY_DESC TABLESPACE D_FRS3	VARCHAR2(16) VARCHAR2(265)	NOT NULL, NOT NULL)
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 8192 PCTING	CREASE 0)	
CREATE TABLE FRS_FACILITY_HISTORY (FACILITY_UIN FINDS_ID FACILITY_CATEGORY MONITORING_STATUS ARCHIVE_DATE DUPLICATE_UIN USER_COMMENT USER_ID TIMESTAMP	VARCHAR2(12) VARCHAR2(12) VARCHAR2(30) VARCHAR2(20) DATE NUMBER(12,0) VARCHAR2(240) VARCHAR2(15) DATE	NOT NULL, NULL, NOT NULL, NULL, NULL, NULL, NULL, NOT NULL, NOT NULL,
SOURCE OPERATION	VARCHAR2(10) VARCHAR2(20)	NOT NULL, NOT NULL)
TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40 STORAGE(INITIAL 57589760 NEXT 5554176 Pc/	, ,	NOT NOLL)
CREATE TABLE FRS_FACILITY_LINKAGE (PARENT_FACILITY_UIN CHILD_FACILITY_UIN TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40 STORAGE(INITIAL 532480 NEXT 8192 PCTING)	VARCHAR2(12) VARCHAR2(12) CREASE 0)	NOT NULL, NOT NULL)
CREATE TABLE FRS_FEEDBACK (
PGM_SYS_ACRNM PGM_SYS_ID FACILITY_UIN FINDS_ID PRIMARY_NAME LOCATION_ADDRESS CITY_NAME COUNTY_NAME	VARCHAR2(15) VARCHAR2(30) VARCHAR2(12) VARCHAR2(12) VARCHAR2(50) VARCHAR2(50) VARCHAR2(30) VARCHAR2(35)	NOT NULL, NOT NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,

```
STATE CODE
                                     VARCHAR2(2)
                                                    NOT NULL.
POSTAL_CODE
                                     VARCHAR2(14)
                                                    NULL,
EPA_REGION_CODE
                                                    NULL,
                                     NUMBER(2,0)
                                                    NULL,
DATA_QUALITY_CODE
                                     VARCHAR2(20)
CREATE DATETIME
                                    DATE
                                                    NOT NULL,
REPORTED DATETIME
                                                    NULL.
                                    DATE
USER ID
                                                    NULL,
                                     VARCHAR2(15)
SOURCE
                                     VARCHAR2(10)
                                                    NULL.
PROCESSING_STATUS
                                     VARCHAR2(20)
                                                    NULL,
USER COMMENT
                                     VARCHAR2(240)
                                                    NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS MAILING ADDRESS (
MAIL UIN
                                     NUMBER(12,0)
                                                    NOT NULL,
DELIVERY POINT
                                     VARCHAR2(50)
                                                    NOT NULL,
SUPPLEMENTAL_ADDRESS
                                     VARCHAR2(30)
                                                    NULL,
CITY NAME
                                     VARCHAR2(30)
                                                    NULL,
STATE_CODE
                                     CHAR(2)
                                                    NOT NULL,
STATE NAME
                                     VARCHAR2(35)
                                                    NULL,
POSTAL_CODE
                                     VARCHAR2(14)
                                                    NULL,
COUNTRY NAME
                               VARCHAR2(44)
                                               NULL.
SOUNDEX CITY NAME
                                                    NULL,
                                    CHAR(4)
                                                    NOT NULL,
TIMESTAMP
                                    DATE
USER ID
                                                    NOT NULL,
                                     VARCHAR2(15)
SOURCE
                                     VARCHAR2(10)
                                                    NOT NULL,
PGM_SYS_ACRNM
                                     VARCHAR2(15)
                                                    NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 16424960 NEXT 499712 PCTINCREASE 0)
CREATE TABLE FRS NAICS (
SOURCE
                                     VARCHAR2(10)
                                                    NULL,
PGM_SYS_ACRNM
                                                    NOT NULL,
                                     VARCHAR2(15)
                                                    NOT NULL,
PGM_SYS_ID
                                     VARCHAR2(30)
NAIC CODE
                                     VARCHAR2(6)
                                                    NOT NULL,
PRIMARY_INDICATOR_CODE
                                    VARCHAR2(1)
                                                    NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
```

CREATE TABLE FRS_ORGANIZATION (
ALTERNATE PHONE	VARCHAR2(30)	NULL,
EMAIL ADDRESS	VARCHAR2(120)	NULL,
FAX PHONE	VARCHAR2(120) VARCHAR2(30)	NULL,
OFFICE_PHONE	VARCHAR2(30) VARCHAR2(30)	NULL,
OWNER TYPE	VARCHAR2(30) VARCHAR2(10)	NULL,
_	` '	*
ORGANIZATION_UIN NAME	NUMBER(12,0)	NOT NULL,
- 1	VARCHAR2(50)	NOT NULL,
DEPARTMENT_NAME	VARCHAR2(50)	NULL,
PARENT_COMPANY_NAME	VARCHAR2(50)	NULL,
DUNS_COMPANY_NUMBER	VARCHAR2(9)	NULL,
EIN	VARCHAR2(14)	NULL,
STATE_BUSINESS_ID	VARCHAR2(30)	NULL,
SOUNDEX_ORG_NAME	CHAR(4)	NULL,
TIMESTAMP	DATE	NOT NULL,
USER_ID	VARCHAR2(15)	NOT NULL,
SOURCE	VARCHAR2(10)	NOT NULL,
PGM_SYS_ACRNM	VARCHAR2(15)	NULL)
TABLESPACE D_FRS3		
PCTFREE 10 PCTUSED 40	~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	
STORAGE(INITIAL 22568960 NEXT 589824 PC	CTINCREASE 0)	
	ND (
CREATE TABLE FRS_ORGANIZATION_DSCF	`	
NOTIFICATION_DATE	DATE	NULL,
NOTIFICATION_DATE ORGANIZATION_UIN	DATE NUMBER(12,0)	NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM	DATE NUMBER(12,0) VARCHAR2(15)	NOT NULL, NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25)	NOT NULL, NOT NULL, NOT NULL, NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50)	NOT NULL, NOT NULL, NOT NULL, NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN DELIVERY_POINT SUPPLEMENTAL_ADDRESS	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN DELIVERY_POINT SUPPLEMENTAL_ADDRESS CITY_NAME	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0) VARCHAR2(50) VARCHAR2(30) VARCHAR2(30) VARCHAR2(30) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN DELIVERY_POINT SUPPLEMENTAL_ADDRESS	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN DELIVERY_POINT SUPPLEMENTAL_ADDRESS CITY_NAME STATE_CODE POSTAL_CODE	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(9) VARCHAR2(50) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL,
NOTIFICATION_DATE ORGANIZATION_UIN PGM_SYS_ACRNM PGM_SYS_ID AFFILIATION_TYPE NAME DEPARTMENT_NAME DUNS_COMPANY_NUMBER PARENT_COMPANY_NAME EIN STATE_BUSINESS_ID MAIL_UIN DELIVERY_POINT SUPPLEMENTAL_ADDRESS CITY_NAME STATE_CODE	DATE NUMBER(12,0) VARCHAR2(15) VARCHAR2(30) VARCHAR2(25) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50) VARCHAR2(50) VARCHAR2(14) VARCHAR2(14) VARCHAR2(30) NUMBER(12,0) VARCHAR2(50) VARCHAR2(30) VARCHAR2(30) VARCHAR2(30) VARCHAR2(30) VARCHAR2(30)	NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL, NULL, NOT NULL, NULL, NULL, NULL, NULL, NULL, NULL,

```
COUNTRY NAME
                               VARCHAR2(44)
                                               NULL.
                                    VARCHAR2(15)
REPORTER_USER_ID
                                                    NOT NULL,
                                                    NOT NULL,
TIMESTAMP
                                    DATE
REPORTER_COMMENT
                                    VARCHAR2(120)
                                                    NULL,
RECIPIENT_USER_ID
                                    VARCHAR2(15)
                                                    NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS ORGANIZATION HISTORY (
ORGANIZATION UIN
                                    NUMBER(12,0)
                                                    NOT NULL,
                                                    NOT NULL,
NAME
                                    VARCHAR2(50)
DEPARTMENT NAME
                                    VARCHAR2(50)
                                                    NULL,
PARENT_COMPANY_NAME
                                    VARCHAR2(50)
                                                    NULL,
DUNS COMPANY NUMBER
                                                    NULL,
                                    VARCHAR2(9)
EIN
                                    VARCHAR2(14)
                                                    NULL,
STATE BUSINESS ID
                                    VARCHAR2(30)
                                                    NULL,
DELIVERY POINT
                                    VARCHAR2(50)
                                                    NOT NULL,
SUPPLEMENTAL_ADDRESS
                                    VARCHAR2(30)
                                                    NULL,
STATE_CODE
                                    VARCHAR2(2)
                                                    NOT NULL,
CITY_NAME
                                    VARCHAR2(30)
                                                    NULL,
STATE NAME
                                    VARCHAR2(35)
                                                    NULL,
POSTAL_CODE
                                    VARCHAR2(14)
                                                    NULL,
COUNTRY NAME
                                               NULL.
                               VARCHAR2(44)
SOUNDEX ORG NAME
                                                    NULL.
                                    CHAR(4)
SOUNDEX_CITY_NAME
                                    CHAR(4)
                                                    NULL,
USER ID
                                    VARCHAR2(15)
                                                    NOT NULL,
TIMESTAMP
                                    DATE
                                                    NOT NULL,
SOURCE
                                    VARCHAR2(10)
                                                    NOT NULL,
                                                    NOT NULL,
OPERATION
                                    VARCHAR2(20)
ALTERNATE PHONE
                                    VARCHAR2(30)
                                                    NULL,
EMAIL ADDRESS
                                    VARCHAR2(120)
                                                    NULL,
FAX PHONE
                                    VARCHAR2(30)
                                                    NULL.
OFFICE PHONE
                                    VARCHAR2(30)
                                                    NULL,
OWNER TYPE
                                    VARCHAR2(10)
                                                    NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS_ORG_AFFILIATION (
ORGANIZATION UIN
                                    NUMBER(12,0)
                                                    NOT NULL.
PGM SYS ACRNM
                                    VARCHAR2(15)
                                                    NOT NULL,
```

```
PGM SYS ID
                                     VARCHAR2(30)
                                                     NOT NULL.
                                                     NOT NULL,
AFFILIATION_TYPE
                                     VARCHAR2(25)
MAIL_UIN
                                     NUMBER(12,0)
                                                     NULL,
TIMESTAMP
                                     DATE
                                                     NOT NULL,
USER ID
                                     VARCHAR2(15)
                                                     NOT NULL,
SOURCE
                                     VARCHAR2(10)
                                                     NULL.
                                DATE
EFFECTIVE_DATE
                                                NULL,
END DATE
                                     DATE
                                                     NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 36249600 NEXT 753664 PCTINCREASE 0)
CREATE TABLE FRS ORG AFF HISTORY (
ORGANIZATION_UIN
                                     NUMBER(12,0)
                                                     NOT NULL,
PGM SYS ACRNM
                                                     NOT NULL,
                                     VARCHAR2(15)
PGM SYS ID
                                     VARCHAR2(30)
                                                     NOT NULL,
AFFILIATION TYPE
                                     VARCHAR2(25)
                                                     NOT NULL,
TIMESTAMP
                                     DATE
                                                     NOT NULL,
USER_ID
                                     VARCHAR2(15)
                                                     NOT NULL,
SOURCE
                                     VARCHAR2(10)
                                                     NOT NULL,
OPERATION
                                     VARCHAR2(20)
                                                     NOT NULL,
                                                NULL,
                                DATE
EFFECTIVE DATE
END DATE
                                     DATE
                                                     NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS_PGM_FACILITY_DSCRP (
NOTIFICATION DATE
                                                     NULL,
                                     DATE
PGM_SYS_ACRNM
                                                     NOT NULL,
                                     VARCHAR2(15)
PGM SYS ID
                                     VARCHAR2(30)
                                                     NOT NULL,
FACILITY UIN
                                     VARCHAR2(12)
                                                     NULL,
FINDS ID
                                     VARCHAR2(12)
                                                     NULL.
FACILITY NAME
                                     VARCHAR2(50)
                                                     NULL.
LOCATION ADDRESS
                                     VARCHAR2(50)
                                                     NOT NULL,
SUPPLEMENTAL_LOCATION
                                                     NULL,
                                     VARCHAR2(30)
CITY_NAME
                                     VARCHAR2(30)
                                                     NULL,
                                                     NOT NULL,
STATE CODE
                                     CHAR(2)
STATE NAME
                                     VARCHAR2(35)
                                                     NULL,
COUNTY_NAME
                                     VARCHAR2(35)
                                                     NULL,
POSTAL CODE
                                     VARCHAR2(14)
                                                     NULL.
COUNTRY_NAME
                                VARCHAR2(44)
                                                NULL,
```

```
CONGRESSIONAL DISTRICT NUMBER
                                    VARCHAR2(2)
                                                    NULL.
LEGISLATIVE_DISTRICT_NUMBER
                                    VARCHAR2(2)
                                                    NULL,
HUC_CODE
                               VARCHAR2(8)
                                               NULL,
FEDERAL_FACILITY_CODE
                                    VARCHAR2(1)
                                                    NULL,
TRIBAL_LAND_CODE
                                                    NULL,
                                    VARCHAR2(1)
TRIBAL LAND NAME
                                    VARCHAR2(52)
                                                    NULL.
DUNS COMPANY NUMBER
                                    VARCHAR2(9)
                                                    NULL,
REPORTER USER ID
                                    VARCHAR2(15)
                                                    NOT NULL,
TIMESTAMP
                                    DATE
                                                    NOT NULL,
REPORTER COMMENT
                                    VARCHAR2(120)
                                                    NULL,
RECIPIENT_USER_ID
                                    VARCHAR2(15)
                                                    NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS PGM FACILITY HISTORY (
PARSED STREET NUMBER
                                    VARCHAR2(8)
                                                    NULL,
PARSED STREET NAME
                               VARCHAR2(50)
                                               NULL,
PGM_SYS_ACRNM
                                    VARCHAR2(15)
                                                    NOT NULL,
PGM_SYS_ID
                                    VARCHAR2(30)
                                                    NOT NULL,
STANZED_PRIM_NAME
                                    VARCHAR2(50)
                                                    NOT NULL,
FACILITY_UIN
                                    VARCHAR2(12)
                                                    NULL,
FINDS_ID
                                    VARCHAR2(12)
                                                    NULL,
PRIMARY NAME
                                                    NULL,
                                    VARCHAR2(50)
LOCAL NAME
                                    VARCHAR2(50)
                                                    NULL,
OTHER NAME
                                    VARCHAR2(50)
                                                    NULL,
PROG_FAC_TYPE
                                                    NULL,
                                    VARCHAR2(75)
PROG_FAC_STATUS
                                    VARCHAR2(10)
                                                    NULL,
LOCATION_ADDRESS
                                    VARCHAR2(50)
                                                    NULL,
SUPPLEMENTAL_LOCATION
                                                    NULL,
                                    VARCHAR2(30)
CITY NAME
                                    VARCHAR2(30)
                                                    NULL,
                                                    NULL,
COUNTY NAME
                                    VARCHAR2(35)
                                                    NOT NULL,
STATE CODE
                                    CHAR(2)
STATE NAME
                                    VARCHAR2(35)
                                                    NULL,
POSTAL CODE
                                    VARCHAR2(14)
                                                    NULL,
EPA_REGION_CODE
                                                    NOT NULL,
                                    NUMBER(2,0)
COUNTRY_NAME
                               VARCHAR2(44)
                                               NULL,
CONGRESSIONAL DISTRICT NUMBER
                                    VARCHAR2(2)
                                                    NULL,
LEGISLATIVE_DISTRICT_NUMBER
                                    VARCHAR2(2)
                                                    NULL,
HUC CODE
                               VARCHAR2(8)
                                               NULL,
FEDERAL FACILITY CODE
                                    CHAR(1)
                                                    NULL.
TRIBAL_LAND_CODE
                                    CHAR(1)
                                                    NULL,
```

TRIBAL_LAND_NAME DATA_QUALITY_CODE DUNS_COMPANY_NUMBER USER_COMMENT USER_ID TIMESTAMP TRANSACTION_USER_ID TRANSACTION_DATE SOURCE OPERATION NEW_UIN TABLESPACE D_FRS2 PCTFREE 10 PCTUSED 30	VARCHAR2(52) VARCHAR2(20) VARCHAR2(9) VARCHAR2(240) VARCHAR2(15) DATE VARCHAR2(15) DATE VARCHAR2(10) VARCHAR2(20) VARCHAR2(12)	NULL, NULL, NULL, NOT NULL, NOT NULL, NULL, NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL, NOT NULL,
STORAGE(INITIAL 104857600 NEXT 10485760	PCTINCREASE 0)	
CREATE TABLE FRS_PGM_MA_AFF (VADCIIAD2(15)	NOT NI II I
PGM_SYS_ACRNM PGM_SYS_ID	VARCHAR2(15) VARCHAR2(30)	NOT NULL, NOT NULL,
AFF TYPE	VARCHAR2(30) VARCHAR2(25)	NOT NULL,
MAIL_UIN	NUMBER(12,0)	NULL,
TIMESTAMP	DATE	NOT NULL,
USER_ID	VARCHAR2(15)	NOT NULL,
SOURCE	VARCHAR2(10)	NULL)
TABLESPACE D_FRS3	V/IRCIII IR2(10)	(CLL)
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 524288 PCTI	NCREASE 0)	
/	1,61,21,22,0)	
CREATE TABLE FRS_PROGRAM_FACILITY (
PRIORITY_CATEGORY	VARCHAR2(15)	NOT NULL,
PGM_SYS_ACRNM	VARCHAR2(15)	NOT NULL,
PGM_SYS_ID	VARCHAR2(30)	NOT NULL,
FACILITY_UIN	VARCHAR2(12)	NOT NULL,
FINDS_ID	VARCHAR2(12)	NULL,
STANDZED_PRIM_NAME	VARCHAR2(50)	NULL,
PRIMARY_NAME	VARCHAR2(50)	NOT NULL,
LOCAL_NAME	VARCHAR2(50)	NULL,
OTHER_NAME	VARCHAR2(50)	NULL,
PROG_FAC_TYPE	VARCHAR2(75)	NULL,
PROG_FAC_STATUS	VARCHAR2(10)	NULL,
SOUNDEX_PRIM_NAME	CHAR(4)	NULL,
SOUNDEX_LOCAL_NAME	CHAR(4)	NULL,
LOCATION_ADDRESS	VARCHAR2(50)	NULL,

SUPPLEMENTAL_LOCATION PARSED_PREDIRECTIONAL_CODE PARSED_STREET_NUMBER PARSED_STREET_NAME SOUNDEX_STREET_NAME PARSED_POST_DIR_CODE CITY_NAME SOUNDEX_CITY_NAME SOUNDEX_CITY_NAME COUNTY_NAME SOUNDEX_COUNTY_NAME SOUNDEX_COUNTY_NAME SOUNDEX_COUNTY_NAME SOUNDEX_COUNTY_NAME STATE_CODE POSTAL_CODE STATE_NAME COUNTRY_NAME EPA_REGION_CODE CONGRESSIONAL_DIST_NUM LEGISLATIVE_DIST_NUM HUC_CODE FEDERAL_FACILITY_CODE TRIBAL_LAND_CODE TRIBAL_LAND_NAME DUNS_COMPANY_NUMBER DATA_QUALITY_CODE USER_COMMENT PRIORITY USER_ID TIMESTAMP SOURCE PROCESSING_STATUS	VARCHAR2(30) VARCHAR2(6) VARCHAR2(8) VARCHAR2(50) NULLI CHAR(4) VARCHAR2(12) VARCHAR2(12) VARCHAR2(30) CHAR(4) VARCHAR2(35) CHAR(4) CHAR(2) VARCHAR2(14) VARCHAR2(35) VARCHAR2(14) NULLI NUMBER(2,0) VARCHAR2(2) VARCHAR2(2) VARCHAR2(2) VARCHAR2(2) VARCHAR2(8) NULLI CHAR(1) CHAR(1) CHAR(1) VARCHAR2(20) VARCHAR2(20) VARCHAR2(20) VARCHAR2(20) VARCHAR2(215) DATE VARCHAR2(10)	NULL,
	` /	,
PROCESSING_STATUS	VARCHAR2(20)	NULL)
TABLESPACE D_FRS1 PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 300032000 NEXT 20	0007680 PCTINCREASE 0)	
/		
CREATE TABLE FRS_PROGRAM_INTE		 .
PGM_SYS_CODE	CHAR(2)	NULL,
PGM_SYS_ACRNM	VARCHAR2(15)	NOT NULL,
PGM_SYS_NAME OFFICE_ACRNM	VARCHAR2(50)	NOT NULL, NULL,
PGM_INTEREST_NAME	VARCHAR2(30) VARCHAR2(100)	NULL, NULL)
TABLESPACE D FRS3	VARCHAR2(100)	NULL)
PCTFREE 10 PCTUSED 40		
TOTTNEE TOTOTOSED 40		

```
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS_RES_CONTACT (
PGM_SYS_ID
                                     VARCHAR2(30)
                                                     NOT NULL,
PGM_SYS_ACRNM
                                     VARCHAR2(15)
                                                     NOT NULL,
AFFILIATION TYPE
                                                     NOT NULL.
                                     VARCHAR2(25)
FULL NAME
                                     VARCHAR2(50)
                                                     NULL,
LAST NAME
                                     VARCHAR2(30)
                                                     NULL.
TITLE
                                     VARCHAR2(30)
                                                     NULL,
HOME PHONE
                                     VARCHAR2(30)
                                                     NULL.
OFFICE_PHONE
                                     VARCHAR2(30)
                                                     NULL,
MOBILE_PHONE
                                     VARCHAR2(30)
                                                     NULL,
FAX PHONE
                                     VARCHAR2(30)
                                                     NULL,
EMAIL_ADDRESS
                                     VARCHAR2(120)
                                                     NULL,
DELIVERY POINT
                                                     NULL,
                                     VARCHAR2(50)
SUPPLEMENTAL ADDRESS
                                     VARCHAR2(30)
                                                     NULL,
                                                     NULL.
CITY NAME
                                     VARCHAR2(30)
STATE CODE
                                     CHAR(2)
                                                     NULL,
STATE_NAME
                                     VARCHAR2(35)
                                                     NULL,
OPER_TYPE
                                     CHAR(2)
                                                     NULL,
POSTAL_CODE
                                     VARCHAR2(14)
                                                     NULL,
COUNTRY NAME
                               VARCHAR2(44)
                                               NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 2007040 NEXT 229376 PCTINCREASE 0)
CREATE TABLE FRS_RES_ERROR (
TABLE_NAME
                                     VARCHAR2(50)
                                                     NULL,
                                                     NULL,
HANDLER_ID
                                     VARCHAR2(30)
ERROR_MESSAGE
                                     VARCHAR2(80)
                                                     NULL,
OPER TYPE
                                     CHAR(2)
                                                     NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 2023424 NEXT 16384 PCTINCREASE 0)
CREATE TABLE FRS_RES_FACILITY (
PRIORITY_CATEGORY
                                                     NOT NULL,
                                     VARCHAR2(15)
PROG FAC TYPE
                                     VARCHAR2(75)
                                                     NULL,
PROG_FAC_STATUS
                                     VARCHAR2(10)
                                                     NULL,
LOCATION ADDRESS
                                     VARCHAR2(50)
                                                     NULL,
SUPPLEMENTAL LOCATION
                                     VARCHAR2(30)
                                                     NULL.
PARSED STREET NUMBER
                                     VARCHAR2(8)
                                                     NULL,
```

```
PARSED PREDIR CODE
                                     VARCHAR2(6)
                                                    NULL.
PARSED_STREET_NAME
                                               NULL,
                               VARCHAR2(50)
PARSED_STREET_SUFFIX
                                     VARCHAR2(12)
                                                    NULL,
PARSED_POSTDIR_CODE
                                     VARCHAR2(6)
                                                    NULL,
CITY NAME
                                     VARCHAR2(30)
                                                    NULL,
STATE CODE
                                     CHAR(2)
                                                    NULL.
                                                    NULL,
STATE NAME
                                     VARCHAR2(35)
COUNTY NAME
                                     VARCHAR2(35)
                                                    NULL.
POSTAL CODE
                                     VARCHAR2(14)
                                                    NULL,
COUNTRY NAME
                               VARCHAR2(44)
                                               NULL.
EPA REGION CODE
                                     NUMBER(2,0)
                                                    NULL,
CONGRESSIONAL_DIST_NUM
                                                    NULL,
                                    CHAR(2)
LEGISLATIVE DIST NUM
                                    CHAR(2)
                                                    NULL,
HUC_CODE
                               CHAR(8)
                                               NULL,
FEDERAL FACILITY CODE
                                     CHAR(1)
                                                    NULL,
TRIBAL LAND CODE
                                                    NULL,
                                    CHAR(1)
TRIBAL LAND NAME
                                     VARCHAR2(52)
                                                    NULL,
DUNS COMPANY NUMBER
                                     VARCHAR2(9)
                                                    NULL,
DATA_QUALITY_CODE
                                     VARCHAR2(20)
                                                    NULL,
PROCESSING_STATUS
                                    CHAR(1)
                                                    NULL,
OPER_TYPE
                                    CHAR(2)
                                                    NULL,
PGM_SYS_ACRNM
                                     VARCHAR2(15)
                                                    NOT NULL,
PGM_SYS_ID
                                     VARCHAR2(30)
                                                    NOT NULL,
FINDS ID
                                     VARCHAR2(12)
                                                    NULL,
STNDZED PRIM NAME
                                     VARCHAR2(50)
                                                    NULL,
                                                    NULL,
PRIMARY NAME
                                     VARCHAR2(50)
LOCAL_NAME
                                     VARCHAR2(50)
                                                    NULL,
OTHER_NAME
                                     VARCHAR2(50)
                                                    NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 6840320 NEXT 352256 PCTINCREASE 0)
CREATE TABLE FRS RES HISTORY (
PGM SYS ACRNM
                                     VARCHAR2(15)
                                                    NOT NULL,
PHASE
                                     VARCHAR2(20)
                                                    NOT NULL,
STATUS
                                     VARCHAR2(20)
                                                    NULL,
START_TIME
                                    DATE
                                                    NULL,
END_TIME
                                    DATE
                                                    NULL,
NUM_OF_PHASES
                               NUMBER(7,0)
                                               NULL)
TABLESPACE D FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
```

```
CREATE TABLE FRS_RES_LINKS (
PARENT_FACILITY_UIN
                                     VARCHAR2(12)
                                                     NOT NULL,
CHILD_FACILITY_UIN
                                     VARCHAR2(12)
                                                     NOT NULL,
OPER_TYPE
                                     VARCHAR2(2)
                                                     NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS RES MAIL (
PGM_SYS_ID
                                                     NOT NULL,
                                     VARCHAR2(30)
PGM_SYS_ACRNM
                                                     NOT NULL,
                                     VARCHAR2(15)
CITY NAME
                                     VARCHAR2(30)
                                                     NULL,
STATE_CODE
                                     CHAR(2)
                                                     NULL,
                                     VARCHAR2(35)
STATE NAME
                                                     NULL,
POSTAL CODE
                                     VARCHAR2(14)
                                                     NULL,
                               VARCHAR2(44)
COUNTRY NAME
                                               NULL.
OPER TYPE
                                     VARCHAR2(2)
                                                     NULL,
DELIVERY_POINT
                                     VARCHAR2(50)
                                                     NULL,
SUPPLEMENTAL_ADDRESS
                                     VARCHAR2(30)
                                                     NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 4194304 NEXT 524288 PCTINCREASE 0)
CREATE TABLE FRS RES ORG (
EFFECTIVE DATE
                               DATE
                                               NULL,
ALTERNATE PHONE
                                     VARCHAR2(30)
                                                     NULL,
EMAIL_ADDRESS
                                     VARCHAR2(120)
                                                     NULL,
FAX PHONE
                                     VARCHAR2(30)
                                                     NULL,
OFFICE_PHONE
                                     VARCHAR2(30)
                                                     NULL,
OWNER_TYPE
                                     VARCHAR2(10)
                                                     NULL,
                                                     NULL,
END DATE
                                     DATE
PGM SYS ID
                                     VARCHAR2(30)
                                                     NOT NULL,
PGM SYS ACRNM
                                                     NOT NULL,
                                     VARCHAR2(15)
AFFILIATION TYPE
                                     VARCHAR2(25)
                                                     NOT NULL,
NAME
                                     VARCHAR2(50)
                                                     NULL,
DEPARTMENT_NAME
                                     VARCHAR2(50)
                                                     NULL,
                                                     NULL,
DUNS_COMPANY_NUMBER
                                     VARCHAR2(9)
PARENT_COMPANY_NAME
                                     VARCHAR2(50)
                                                     NULL,
EIN
                                     VARCHAR2(14)
                                                     NULL,
STATE BUSINESS ID
                                     VARCHAR2(30)
                                                     NULL.
DELIVERY_POINT
                                     VARCHAR2(50)
                                                     NULL,
```

SUPPLEMENTAL_ADDRESS CITY_NAME STATE_CODE STATE_NAME POSTAL_CODE COUNTRY_NAME SOURCE OPER_TYPE TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40 STORAGE(INITIAL 4259840 NEXT 3440)	VARCHAR2(30) VARCHAR2(30) CHAR(2) VARCHAR2(35) VARCHAR2(14) VARCHAR2(44) VARCHAR2(10) VARCHAR2(2)	NULL, NULL, NULL, NULL, NULL, NULL, NULL, NULL,
CREATE TABLE FRS_RES_SIC (SOURCE PGM_SYS_ID PGM_SYS_ACRNM SIC_CODE PRIMARY_INDICATOR_CODE OPER_TYPE TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40	VARCHAR2(25) VARCHAR2(30) VARCHAR2(15) CHAR(4) CHAR(1) CHAR(2)	NULL, NOT NULL, NOT NULL, NOT NULL, NULL, NULL)
STORAGE(INITIAL 737280 NEXT 65536	PCTINCREASE 0)	
CREATE TABLE FRS_RES_STATUS (PGM_SYS_ACRNM PHASE CURRENT_STATUS START_TIME END_TIME NUM_OF_PHASES	VARCHAR2(15) VARCHAR2(20) VARCHAR2(20) DATE DATE NUMBER(7,0) NULL	NOT NULL, NOT NULL, NULL, NULL, NULL,
TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40 STORAGE(INITIAL 532480 NEXT 8192 I	PCTINCREASE 0)	
CREATE TABLE FRS_SIC (SOURCE PGM_SYS_ACRNM PGM_SYS_ID SIC_CODE PRIMARY_INDICATOR_CODE TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40	VARCHAR2(25) VARCHAR2(15) VARCHAR2(30) CHAR(4) CHAR(1)	NULL, NOT NULL, NOT NULL, NOT NULL, NULL)

```
STORAGE(INITIAL 13082624 NEXT 442368 PCTINCREASE 0)
CREATE TABLE FRS_SIC_NAIC_DSCRP (
NOTIFICATION_DATE
                                     DATE
                                                     NULL,
PGM_SYS_ACRNM
                                                     NOT NULL,
                                     VARCHAR2(15)
                                                     NOT NULL.
PGM SYS ID
                                     VARCHAR2(30)
                                                     NULL,
SIC CODE
                                     CHAR(4)
NAIC CODE
                                     VARCHAR2(6)
                                                     NULL.
PRIMARY_INDICATOR_CODE
                                     CHAR(1)
                                                     NULL,
REPORTER USER ID
                                     VARCHAR2(15)
                                                     NOT NULL,
TIMESTAMP
                                     DATE
                                                     NOT NULL,
REPORTER_COMMENT
                                     VARCHAR2(120)
                                                     NULL,
RECIPIENT USER ID
                                     VARCHAR2(15)
                                                     NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS USERID HISTORY (
USERID
                                     VARCHAR2(15)
                                                     NOT NULL,
USERPW
                                     VARCHAR2(30)
                                                     NOT NULL)
TABLESPACE D_FRS3
PCTFREE 10 PCTUSED 40
STORAGE(INITIAL 532480 NEXT 8192 PCTINCREASE 0)
CREATE TABLE FRS USER REGISTRY (
                                                     NULL,
PW EXPIRE DATE
                                     DATE
LAST LOGON TIME
                                     DATE
                                                     NULL,
LAST_UPDATE_TIME
                                     DATE
                                                     NULL,
USER_STATUS
                                     VARCHAR2(1)
                                                     NOT NULL,
EMAIL_ADDRESS
                                     VARCHAR2(120)
                                                     NULL,
USER ID
                                     VARCHAR2(15)
                                                     NOT NULL,
USER PW
                                     VARCHAR2(20)
                                                     NOT NULL,
FIRST NAME
                                     VARCHAR2(20)
                                                     NOT NULL,
LAST NAME
                                     VARCHAR2(30)
                                                     NOT NULL,
COMPANY NAME
                               VARCHAR2(30)
                                               NOT NULL,
                                                     NOT NULL,
USER_CATEGORY
                                     VARCHAR2(10)
MAIL_ADDRESS
                                     VARCHAR2(30)
                                                     NULL,
MAIL CITY NAME
                                     VARCHAR2(30)
                                                     NULL,
MAIL POSTAL CODE
                                     VARCHAR2(14)
                                                     NULL,
MAIL_STATE_CODE
                                     VARCHAR2(2)
                                                     NULL,
TITLE
                                     VARCHAR2(30)
                                                     NULL.
TELEPHONE_NUMBER
                                     VARCHAR2(30)
                                                     NULL,
```

FAX_NUMBER TABLESPACE D_FRS3 PCTFREE 10 PCTUSED 40	VARCHAR2(30)	NULL)
STORAGE(INITIAL 532480 NEXT 8192	PCTINCREASE (1)	
/	TOTH VEREZIBLE 0)	
CREATE TABLE PLACE_REFERENCE (
STATUS_CODE	CHAR(1)	NULL,
STATUS_CD_TS	VARCHAR2(8)	NULL,
COUNTRY_IDENTIFIER	NUMBER(7,0)	NULL,
COUNTRY_CODE	CHAR(2)	NULL,
COUNTRY_NAME	VARCHAR2(52) NUL	L,
STATE_IDENTIFIER	NUMBER(7,0)	NULL,
STATE_CODE	CHAR(2)	NULL,
US_STATE_ABBREV_NM	CHAR(2)	NULL,
STATE_NAME	VARCHAR2(52)	NULL,
EPA_REGION_ID	NUMBER(7,0)	NULL,
EPA_REGION_CODE	CHAR(2)	NULL,
EPA_REGION_NAME	VARCHAR2(20)	NULL,
COUNTY_IDENTIFIER	NUMBER(7,0)	NULL,
COUNTY_CODE	CHAR(3)	NULL,
COUNTY_NAME	VARCHAR2(52)	NULL)
TABLESPACE D_FRS3		
PCTFREE 10 PCTUSED 40		
STORAGE(INITIAL 532480 NEXT 65536	5 PCTINCREASE 0)	